




## K-BUS □ □





□ □      □ □  
□    □ □  
□      □  
□  
□  
□      □  
□

□ □                      □ □                      □ □   □   □                      □ □                      □   □   □   □ □

□ □                      □ □ !                      !                      !                      □ □ □                      □ □   □   k

□ □                      N-□ Zk&:   □ □                                              □   □ □

□ □                      □ □   □ □                                              □ □ □   □                      □ □   □                      □

□



[illegible]



|     |         |           |
|-----|---------|-----------|
| □   | □       | □         |
|     | □ □     |           |
|     | □       |           |
|     | □ □     |           |
| □ □ | □ □     |           |
|     | □ □ □   | ®         |
|     |         | ®         |
| □ □ | □ □     | □ □       |
|     | □ □ □   |           |
|     | □ □ □   | -         |
| □   |         | □ □ □ □   |
|     | □ □ □ □ | □ □ □ □   |
|     | □ □ □ □ | □ □       |
|     | □       |           |
|     | □ □ □   | □ □ □ □ □ |
| □ □ | □       | “ - -     |
|     | □       | “ - -     |
|     | □ □     | “ - -     |
| □   | □ □     | □ □ □     |
|     |         | □         |
| □   | ŧ Ô     |           |
|     |         |           |

□ □ □

□ □ □ □ □ - □ k


□ □ □ □ □ □ □ □ □ □ □ k

|     |               |   |
|-----|---------------|---|
| □   | □             | □ |
|     | □ □           |   |
|     | □             |   |
|     | □ □           |   |
| □ □ | □ □ □         |   |
|     | □             |   |
|     | □ □           |   |
| □   | □ □ □ □ □ □   |   |
|     | □             |   |
|     | □ □ □ □ □ □ □ |   |
| □ □ | □ " - -       |   |
|     | □ " - -       |   |
|     | □ □ " - -     |   |
| □   | □ □ □ □ □     |   |
|     | □ □ □ □       |   |
| □   | ō             |   |
|     |               |   |





□



□ □ □ □



F

F

h □ □

4 □ □ □ □ □ □

3 □ □ □ □ □ □



□ □ □ □

F □ □

F

h

4 □ □

3 □

□

□

|     |       |       |     |
|-----|-------|-------|-----|
| □ □ | □ □ □ | □ □ □ | □ □ |
|     |       |       |     |

□

□

□

□ □

k

□ □

□

□ □

k

□ □

□ □ □

□

□ □

□ □

□ □

□ □

□

□ □

□

□ □ □

U

□ □

□ □ □

□ □ □

k

□ □ □

□

□ □ □ □

□ □

□

U □ □ !

!

k

□ □

□

□

□ □

□ □

□ k

□ □

□

□ □

□

k

□

□

□ □

□ □

□

□ □

□ □

k

□

□

□

□

□ □ □

!

□ □ !

! □ □ !

□

□

□

□

□

□

□

□

□ □ □

□

□

□

□ □

□

□

□ □ □

□



□

□ □

□ □

□ я

□ □

□

□

□

□ □

□

□

□

□

k

## 1.1.2 KNX Gateway for IR,Flush mounted,2-Fold > DCA Note

### DCA Note



Remote IR code learning and downloading must use IR Learner via DCA software. In order to use DCA normally, ETS must run in compatibility mode, which should be activated via ETS Apps in ETS5.

General

□ k □ □ □

□ □ □ □

□

□ □

□ □

□ □ □ □

k □

□

□ □ □

□ □

U

□

k

Apps + ↺

3 active / 11 installed

Name


Vendor

Version

id

| Name                                 | Vendor     | Version | id |
|--------------------------------------|------------|---------|----|
| KNX Gateway for IR Configuration APP | Video Star | 1.0.0.0 |    |
| Labels                               | KNX Assets |         |    |





□ □

□

□

□ □

k

□ □

□ □

□ □

□

□

U

□ Ç

k

□ □

□ □

□ □

k

□ □

□ □ □ □

□

□

□

□ □

□ k

” ”

□

□

□ □ □

k

□

□ □ □

□

□ □ □ □

k

□ □

□

” ”

□

□ □

□

□

□

□

□

□

□

□ □ k

□ □

□

□

□ □

□ □


□ □ k

□


□ □

□ □

□ □ k



□ □ □ k



□ □ □ k

--- KNX Gateway for IR,Flush mounted,2-Fold > Channel 1 > Universal IR control setting

|                              |              |   |
|------------------------------|--------------|---|
| DCA Note                     | IR control 1 | ✓ |
| + General                    | IR control 2 | ✓ |
|                              | IR control 3 | ✓ |
|                              | IR control 4 | ✓ |
| - Channel 1                  | IR control 5 | ✓ |
|                              | IR control 6 | ✓ |
| Universal IR control setting | IR control 1 | ✓ |





□ □ □ □ □ k □ □

□ □ □ □ □ k □ M □ □ □ □ □ k

□ □

□ □ k □ □

□ □ □ □ □ □ □ □ □ □ k

□ □

U □ □ □ □ □ k

U □ □ □ □ □ k

□ □ k

□ □ □ □ □ □ k □ □

□


**GVS**

**K-BUS**



|                          |                                    |                                              |
|--------------------------|------------------------------------|----------------------------------------------|
| Heat-Fan auto-No Swing   | Object datatype of 1byte fan speed | <input type="radio"/> Fan stage (DPT_5.100)  |
| Heat-Fan low-No Swing    |                                    | <input type="radio"/> Percentage (DPT_5.001) |
| Heat-Fan medium-No Swing | <b>Fan speed control setting</b>   |                                              |
| Heat-Fan high-No Swing   | Control value for fan speed auto   | 0 %                                          |
| Heat-Fan auto-Swing      | Control value for fan speed        |                                              |

|                               |                                             |                                     |
|-------------------------------|---------------------------------------------|-------------------------------------|
| Heat-Fan low-Swing            | <b>Code control function</b>                |                                     |
| Heat-Fan medium-Swing         | Auto mode                                   | <input checked="" type="checkbox"/> |
| Heat-Fan high-Swing           | Control value for auto [0..255]             | 0                                   |
| Cool-Fan auto-No Swing        | Status value for auto [0..255]              | 0                                   |
| Cool-Fan low-No Swing         | Heating mode                                | <input checked="" type="checkbox"/> |
| Cool-Fan medium-No Swing      | Control value for heating [0..255]          | 1                                   |
| Cool-Fan high-No Swing        | Status value for heating [0..255]           | 1                                   |
| Cool-Fan auto-Swing           | Cooling mode                                | <input checked="" type="checkbox"/> |
| Cool-Fan low-Swing            | Control value for cooling [0..255]          | 3                                   |
| Cool-Fan medium-Swing         | Status value for cooling [0..255]           | 3                                   |
| Cool-Fan high-Swing           | Fan mode                                    | <input checked="" type="checkbox"/> |
| Fan-Fan speed-Wind            | Control value for fan [0..255]              | 9                                   |
|                               | Status value for fan [0..255]               | 9                                   |
| Dehumidification-Fan speed... | Dehumidification mode                       | <input checked="" type="checkbox"/> |
| Control mode                  | Control value for dehumidification [0..255] |                                     |
| Sequence mode                 | Status value for dehumidification [0..255]  |                                     |



□ L k □ □

□ □ k □ □ L k

o □ o □ □ k □ □ □ k

□ □ L k □ □

□ □ L k □ □

□ □ □ k □ U □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ k

□ □ □ k □ □

-

-

-

□ k □ □

...

□ □ □ k □ □

...

□ □ □ □ □ k □ □

□ □ □ □ k □ □

□ □ □ k □ □ □ □ k □ □ □ □ □

□ □ □ □ k □ □

-

-

-

□ □

□ □ k □ □

□ □

□ □

□ □ □ k

□ k ! □ □ ! ! □ □ □


k □ □ □ □ □ k □ □

□ □ □ □ □ □ k □ □

” ”

□ □ □ □ □ □ □ □ □

k □ □




□ □ □ □ □ □ k □ □

” ”

□ □ □ □ □ □ □ □

□ k □ □




□ □ □ k □ □

” ”


□ □ □ □ □ k □ □

” ”

□ □ □ k □ □



□ □ k □ □



□ □ k

” ”

□ □ □ k □ □

” ”

□ □ k □

□

□ □ □ L k □ □ □ □ □

U □ □ ! ! □ □ □ □ □ □ □ □ □ □

□ □ □ □ □ k □ □ □ □ □ □ □ □ U

k

KNX Gateway for IR configuration C:\Users\admin\Desktop\IR PC 软件\大会.IRPrj

物理地址:

下载红外码

Language(语言)

| 制冷-自动-19度 | 描述 | 功能        | 频率       | 脉冲计数 | 红外码编号 |
|-----------|----|-----------|----------|------|-------|
| 制冷-自动-20度 | 大会 | 制冷-自动-16度 | 33.21KHZ | 327  | 21    |
| 制冷-自动-21度 |    |           |          |      |       |
| 制冷-自动-22度 |    |           |          |      |       |
| 制冷-自动-23度 |    |           |          |      |       |
| 制冷-自动-24度 |    |           |          |      |       |
| 制冷-自动-25度 |    |           |          |      |       |
| 制冷-自动-26度 |    |           |          |      |       |
| 制冷-自动-27度 |    |           |          |      |       |
| 制冷-自动-28度 |    |           |          |      |       |



□ □ я

□ □ □ L U k □ □ □ □


□ □ □ □ k □ □ □ □

k





□ □ □ □ □ L k □ □



□ □ □ □ □ k □ □ □ L □ □ ç □

□ □ я □ □ □ □ L k

U □ □ □ □ □ □ □ □ L k


$\square \quad \square \quad \square \quad \square \quad L \quad k$

## --- KNX Gateway for IR, Flush mounted, 2-Fold &gt; Sequence mode &gt; Sequence mode setting

|           |                         |                                     |
|-----------|-------------------------|-------------------------------------|
| DCA Note  | Sequence combination 1  | <input checked="" type="checkbox"/> |
|           | Sequence combination 2  | <input checked="" type="checkbox"/> |
| + General | Sequence combination 3  | <input checked="" type="checkbox"/> |
|           | Sequence combination 4  | <input checked="" type="checkbox"/> |
|           | Sequence combination 5  | <input checked="" type="checkbox"/> |
|           | Sequence combination 6  | <input checked="" type="checkbox"/> |
|           | Sequence combination 7  | <input checked="" type="checkbox"/> |
|           | Sequence combination 8  | <input checked="" type="checkbox"/> |
|           | Sequence combination 9  | <input checked="" type="checkbox"/> |
|           | Sequence combination 10 | <input checked="" type="checkbox"/> |
|           | Sequence combination 11 | <input checked="" type="checkbox"/> |
|           | Sequence combination 12 | <input checked="" type="checkbox"/> |
|           | Sequence combination 13 | <input checked="" type="checkbox"/> |
|           | Sequence combination 14 | <input checked="" type="checkbox"/> |
|           | Sequence combination 15 | <input checked="" type="checkbox"/> |
|           | Sequence combination 16 | <input checked="" type="checkbox"/> |

## --- KNX Gateway for IR, Flush mounted, 2-Fold &gt; Sequence mode &gt; Sequence combination 1


|                        |                                     |                                                                                        |
|------------------------|-------------------------------------|----------------------------------------------------------------------------------------|
| DCA Note               | Description (max 30 characters)     |                                                                                        |
| General                | Object datatype of trigger sequence | <input checked="" type="radio"/> 1bit [On/Off] <input type="radio"/> 1byte [Scene No.] |
| Channel 1              | Trigger value                       | 1 [On]                                                                                 |
| Channel 2              | Enable step 1 command               | <input type="radio"/> Disable <input checked="" type="radio"/> Enable                  |
| Sequence mode          | IR code NO. for emitting [1..300]   | 1                                                                                      |
| Sequence mode setting  | Emitting channel                    | <input checked="" type="radio"/> CH1 <input type="radio"/> CH2                         |
| Sequence combination 1 | Delay time for emitting [0..255]    | 0 *0.1s                                                                                |
|                        | Count of emitting [1..100]          | 1                                                                                      |
| Sequence combination 2 | Enable step 2 command               | <input type="radio"/> Disable <input checked="" type="radio"/> Enable                  |
| Sequence combination 3 | IR code NO. for emitting [1..300]   | 2                                                                                      |
| Sequence combination 4 | Emitting channel                    | <input checked="" type="radio"/> CH1 <input type="radio"/> CH2                         |
| Sequence combination 5 | Delay time for emitting [0..255]    | 1 *0.1s                                                                                |
| Sequence combination 6 | Count of emitting [1..100]          | 1                                                                                      |




□ □ □      □      □      k □ □      □ □ □      k

□ □ □ □      M      k □ U      □ □ □      □      □      M      □      □

□      !      □ □ !      □ !      □ k



□ □ o      □ □ □      □      o      □      k □ □      □      k




□ □ □      □      k      □ □

• •



□ □ □      □      □      □

□      □      □ □

□      □      □ □




M      M      k □ □



GVS

K-BUS





□

□

□


□

□

□ □

k

□ □




□ □

□ □ □

□ □ □ □

k □ □



□

□

□

□

□

□

□ □

□

□

k □



Diagram illustrating the decomposition of a 3x3 grid into 1x1 and 2x2 subgrids. The top row shows 1x1, 2x2, 1x1, 2x2, 1x1, 2x2, 1x1, 2x2, 1x1. The middle row shows 1x1, 2x2, 1x1, 2x2, 1x1, 2x2, 1x1, 2x2, 1x1. The bottom row shows 1x1, 2x2, 1x1, 2x2, 1x1, 2x2, 1x1, 2x2, 1x1. The total number of 1x1 subgrids is 9, and the total number of 2x2 subgrids is 4.

[illegible]







□

□ □ □

□ k □

,

□

,





| Number ^ | Name              | Object Function            | Description | Group Address | Length  | C | R | W | T | U | Data Type    | Priority |
|----------|-------------------|----------------------------|-------------|---------------|---------|---|---|---|---|---|--------------|----------|
| 162      | Current detection | Switch ON/OFF              |             |               | 1 bit   | C | R | - | T | - | switch       | Low      |
| 163      | Current detection | Current value(mA)          |             |               | 2 bytes | C | R | - | T | - | current (mA) | Low      |
| 164      | Current detection | CH1-Internal switch ON/OFF |             |               | 1 bit   | C | - | W | - | U | switch       | Low      |
| 165      | Current detection | CH1-External error report  |             |               | 1 bit   | C | R | - | T | - | alarm        | Low      |
| 166      | Current detection | CH2-External switch ON/OFF |             |               | 1 bit   | C | - | W | - | U | switch       | Low      |
| 167      | Current detection | CH2-External error report  |             |               | 1 bit   | C | R | - | T | - | alarm        | Low      |